

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended): A method for reducing the residual image effect of a liquid crystal display after turned off, comprising the steps of:
transmitting an image signal to the liquid crystal display by means of a timing controller after turning off a backlight of the liquid crystal display;
transmitting a control signal to the liquid crystal display by means of the timing controller after turning off an image data transmission; and
turning on a plurality of thin film transistors on the liquid crystal display after turning off the image data transmission to discharge residual charges.
2. (Original): The method of claim 1, further comprising the step of:
turning off a power to the liquid crystal display.
3. (Original): The method of claim 1, wherein the step of transmitting an image signal is performed before turning off the image data transmission.
4. (Original): The method of claim 1, wherein the step of transmitting a control signal is performed before turning off the power to the liquid crystal display.
5. (Original): The method of claim 1, wherein the image signal comprises a white image signal.
6. (Original): The method of claim 1, wherein the image signal comprises a black image signal.
7. (Original): The method of claim 1, wherein the liquid crystal display further comprises a source driver and a gate driver.
8. (Original): The method of claim 7, wherein the gate driver is used to turn on the

thin film transistors.

9. (Currently Amended): A method for reducing residual image effect applied to a liquid crystal display, comprising the steps of:

- turning off a backlight of the liquid crystal display;
- transmitting an image signal to the liquid crystal display by means of a timing controller;
- turning off an image data transmission;
- transmitting a control signal to the liquid crystal display by means of the timing controller;
- turning on a plurality of thin film transistors on the liquid crystal display after turning off the image data transmission to discharge residual charges; and
- turning off a power to the liquid crystal display.

10. (Original): The method of claim 9, wherein the image signal comprises a white image signal.

11. (Original): The method of claim 9, wherein the image signal comprises a black image signal.

12. (Original): The method of claim 9, wherein the liquid crystal display further comprises a source driver and a gate driver.

13. (Original): The method of claim 12, wherein the gate driver is used to turn on the thin film transistors on the liquid crystal display.

14. (Currently Amended): A system for reducing the residual image effect of a liquid crystal display after turned off, comprising:

- a timing controller for transmitting an image signal and a control signal;
- a source driver electrically coupled with the timing controller, wherein the source driver further has a plurality of source lines;
- a gate driver electrically coupled with the timing controller; and
- a plurality of thin film transistors electrically coupled to the source driver and the gate

driver,

wherein the timing controller transmits the image signal to the source driver in a first period causing a voltage of the thin film transistors to be substantially close to a voltage of a common voltage generator, and the timing controller transmits the control signal to the gate driver to turn on the thin film transistors after turning off an image data transmission in a second period enabling a plurality of charges in the thin film transistors to discharge such that residual charges are discharged via the source lines.

15. (Currently Amended): The system of claim 14, wherein the first period begins when a backlight of the liquid crystal display is turned off and ends when ~~the~~an image data transmission is turned off.

16. (Cancelled)

17. (Original): The system of claim 14, wherein the image signal comprises a black image signal.

18. (Original): The system of claim 14, wherein the image signal comprises a white image signal.